


## Leak Detection Sensors

- ☒ Compact Size
- ☒ Low Cost
- ☒ Reliable
- ☒ Hydrocarbon Detection

Warrick® Leak Detection Sensors are designed for single wall piping, sump alarms and other small areas. Combine with Warrick Monitoring Panels for complete leak detection systems.

DLP-1 & DLP-2



Designed to detect presence of liquid in sumps, attached access pipes, annular spaces, or locations requiring a small float-operated sensor. Two models to fit 1-1/2" and 2" standard piping.

DWP-25




Designed for use in the annular space of double wall fiberglass tanks to detect the presence of conductive liquid. When combined with Warrick DMS or TA alarm panel, DWP-25 sensors can detect the presence of water or other conductive liquids in normally dry annular spaces.

DFP-25




Designed for use in the annular space of double wall fiberglass tanks to detect hydrocarbon liquids. When hydrocarbons are present, a hydrocarbon wax pellet dissolves and closes a spring-loaded switch to signal a leak. This sensor is not reusable after exposure to hydrocarbons.

SVP-2



Designed to monitor hydrocarbon vapors in wells or sumps by absorbing the vapors and triggering a switch. Should not be used where vapors are continuously present. Fits in standard 2" pipe with cover.

DSP-2



Utilizes conductivity probes and a reed switch based float switch to detect the presence of liquid and differentiate between hydrocarbons and water. When combined with Warrick DMS or TA two-channel alarm panel, the DSP-2 can discriminate between water and hydrocarbon liquids causing fault condition.

### How to Order

Order by Part Number (same as Series Name for these products).

Series	Body Components	Number of Sensor Wires	Wire Length	O.D.	Part Number
DLP-1*	Buna-N float, Stainless Steel and plastic housing	2 (N.O. in resting position)	16 ft.	1.22"	DLP-1
DLP-2*				1.88"	DLP-2
DSP-2*					DSP-2
DWP-25	Stainless Steel probes in plastic housing	2	25 ft.	.625"	DWP-25
DFP-25	Spring-loaded switch, plastic housing, wax pellet	2	25 ft.	.625"	DFP-25
SVP-2	Chemical-resistant plastic and Stainless Steel housing	2	16 ft.	2"	SVP-2

\* EPA Approved when used with Warrick TA or DMS panel. See pages E-27 and E-28 respectively.

### Applications

- Above Ground Storage Tanks
- Underground Storage Tanks
- Sumps
- Dry Annular Spaces